

SLIPRING Type PRG-90 50 A

TECHNICAL SHEET **3.8**



MAIN PERFORMANCES

- EXECUTION Without housing. It is necessary that housing has to be realized by end user according to the armonized rules to
- POSITIONING Vertical axis
- INSIDE PASSAGE 42 mm diameter through steel pipe for the passage of
- CONNECTIONS Directly on the terminal box for the rings and on the
- BRUSHES 50 A blade or copper graphite
- EXECUTIONS From 4 to 14 rings 50 A
- ARMONIZED RULES EN 60947-5-1 EN 60529
EEC 73/23 - EEC 89/336 - EEC 89/392 Directive
- MARKING CE

ELECTRICAL FEATURES

- NOMINAL VOLTAGE 660 V AC - DC
- NOMINAL CURRENT Ith 50 A
- PROTECTION DEGREE IP 00
- MAX ROTATING SPEED 30 revs/min
- TEST VOLTAGE 2,5 kV
- OPERATING TEMPERATURE -20 °C ÷ +60 °C

STANDARD TYPES

STANDARD 50 A

N° rings	F	G	H	P	
4	189	49	210	80	mm
6	235	49	250	120	mm
8	281	39	280	160	mm
10	304	49	330	200	mm
12	350	49	370	240	mm
14	396	39	400	280	mm

DIMENSIONS

