

SLIPRING Type PZG

TECHNICAL SHEET 3.7



MAIN PERFORMANCES

- EXECUTION Without housing. It is necessary that housing has to be realized by end user according to the armonized rules to assure a suitable protection
- POSITIONING A vertical one is to prefer, fixing through 3 ties M10 on both ends
- INSIDE PASSAGE Diameter 196 mm suitable for big pipe mounting
- CONNECTIONS Directly on the terminal box for the rings and to the brush holder terminals
- BRUSHES 50 A blade or copper graphite
- EXECUTIONS From 4 to 26 rings 50 A
- ARMONIZED RULES EN 60947-5-1 EN 60529
EEC 73/23 - EEC 89/336 Directive
- MARKING CE

ELECTRICAL FEATURES

- NOMINAL VOLTAGE 660 V AC - DC
- NOMINAL CURRENT Ith 50 A
- PROTECTION DEGREE IP 00
- MAX ROTATING SPEED 20 revs/min.
- TEST VOLTAGE 2,5 kV
- OPERATING TEMPERATURE -20 °C ÷ +60 °C

STANDARD TYPES

	H = mm	F = mm	50 A N° rings
	192	143	4
	223	189	6
	254	212	8
	285	235	10
	316	281	12
	347	304	14
	378	327	16
	409	373	18
	440	396	20
	471	419	22
	502	465	24
	533	488	26

DIMENSIONS

